CITY OF CARMEL RIGHT-OF-WAY PERMIT

PERMIT NUMBER: _____

TODAY'S DATE:	ESTIMATED DATE OF WORK:		
APPLICANT (Person doing the work)			
COMPANY:			
ADDRESS:			
PHONE:	EMAIL PERMIT TO:		
CUSTOMER:			
ADDRESS:			
PHONE:			
ADDRESS OF BROLLET	r.		
ADDRESS OF PROJECT	RK (check all that apply)		
ROAD BORE	DRIVEWAY REPLACEMENT		
CONSTRUCTION ENTRA	RANCE LANE CLOSURE		
STREET CUT	ROAD CLOSURE		
OTHER			
DESCRIPTION:			
TYPE OF SURFACE CUT (if applicable):			
NOTE: OPEN CUTS IN PAVEMENT REQUIRE BOARD OF PUBLIC WORKS (BPW) APPROVAL			
USE OF HEAVY EQUIPMENT YES NO			
DRAWING ATTACHED YES NO			
*NOTE: ON REVERSE SIDE OF THIS PERMIT, PROVIDE NAMES AND CONTACTS OF ALL SUB-CONTRACTORS INVOLVED			
SURETY BOND . Please	e see Item #1 of the Right-of-Way Conditions.		
BONDING COMPANY:			
BONDING NUMBER:			
EXPIRATION DATE:			
As applicant for this Right-of-Way Permit, I understand and agree to all of the specifications and			
	conditions listed on the attached sheet.		
(Applicant's Signature)	(Print Name)		
PERMIT GRANTED BY:	: DATE ISSUED: (City Official)		
COMMENTS:	(City Official)		
REPAIR WORK INSPECTED AND APPROVED			
I have inspected the repair of the above right-of-way and find it to be completely satisfactory.			
	(City Inspector) (Date Released)		

CONDITIONS OF RIGHT-OF-WAY/STREET CUT PERMIT

- The applicant is required to post an open bond (License and Permit type) to the City of Carmel. The amount will be determined by the Right-of-Way Inspector based upon possible damage values.
- 2. Asphalt pavements shall be saw cut. Flowable fill with 12" of concrete and 1 1/2 asphalt. All seams shall be tack coated and shall be ironed as necessary to provide a perfect joining of the patch with the surrounding pavement. No cold mix asphalt to be used except as temporary patches.
- 3. Concrete pavements shall be saw cut. The new concrete patch shall be placed using at least 4000# concrete. The edges of the adjoining pavement shall be coated with an epoxy adhesive intended for concrete patching. The patched area shall be properly barricaded for at least seven days and the patch shall be treated with two coats of a curing compound or a curing membrane.
- 4. All ditches disturbed by excavation shall be properly graded and sodded. All excavations within 5' of edge of pavement shall be filled with a granular fill material with 12" of top soil.
- 5. All grassed areas shall be provided with 12" to 16" of good topsoil and sodded with high-quality bluegrass sod equal to other existing grass.
- 6. Upon completion of all repairs, the applicant shall request inspection from the City Engineer's office. Upon inspection, if all repairs are satisfactory, including sod, if required, being maintained and watered for 14 days, the inspector shall sign the release at the bottom of this permit.
- 7. If the workmanship is deemed, by the City Engineer and/or his Inspector, to be questionable, the City shall reserve the right to withhold release for up to one year from the date of repair.
- 8. The City of Carmel will hold the applicant directly responsible for all work done.
- 9. The City Engineer's office is to be notified upon start of pavement repair so that an inspector may observe the placement of patch materials. Failure to notify may result in removing and replacing repair. A minimum of one hour notice is required.

City of Carmel

Caleb Warner
Right-of-Way Inspector
Department of Engineering
(317) 571-2677 Fax (317) 571-2439 Cell (317) 714-8908
One Civic Square Carmel, IN 46032
cwarner@carmel.in.gov